



SPECIFICATIONS  
**AKCV30**  
 CENTRAL VACUUMS

**CENTRAL VACUUM POWER UNIT**

- **Motor**  
Two stage 120 volt, double ball bearing with tangential bypass discharge and thermoset fan end bracket. 9.7 amps.
- **Power Unit Body**  
Durable textured powder coated all steel body.
- **Performance**  
CFM at 2" opening: 112  
Water Lift: 106"  
Air Watts: 409
- **Collection**  
5 gallon disposable collection bag.
- **Recommended Home Size**  
Homes up to 2,800 square feet.
- **Mounting**  
Includes metal mounting bracket and an extra utility inlet. Unit does not exhaust to the outside.
- **Shipping Information**  
UPC: 0-83162-  
Shipping Weight: lbs.



<b>PROJECT</b>							<b>ARCHITECT</b>			
<b>LOCATION</b>							<b>ENGINEER</b>			
<b>CONTRACTOR</b>							<b>SUBMITTED BY</b>			<b>DATE</b>
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



**U.S.:** 820 Lincoln Drive  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 877-304-3785  
 Fax: (610) 696-8048

**Canada:** 110 Glidden Road  
 Brampton, Ontario L6T 2J3  
 Tel: (905) 456-2033  
 Fax: (905) 456-1015